

Omnia Processor Comparison

FEATURES	Omnia.11	Omnia.9	Omnia.7	Omnia ONE.SG	Omnia ONE FM
RU	4	3	2	1	1
POWER SUPPLIES	1	2 hot-swappable	2 internal	1	1
AM	no	yes	no	no	no
FM	yes	yes	yes	yes	yes
HD/DAB	yes (Option)	Yes (Option)	yes (Option)	no	no
INTERNAL STREAM PROC	no	Yes (included with HD)	yes (Option)	no	no
INTERNAL STREAM FORMAT	no	MP2, MP3, AAC, WMA	MP2, MP3, AAC, WMA	no	no
INTERNAL BACKUP PLAYER	no	yes	no	not applicable	not applicable
NOTES:	FM with Option for HD1. Separate limiters for FM and HD.	AM/FM OR dual FM OR FM with options for 3 x HD+Streaming. Individual processors for each program out. Up to 4 programs. Many configurations possible	Handles 1 stereo program for FM with option of FM + HD 1 + streaming. Separate processors for FM, HD, Streaming	not applicable	One stereo FM program, but can be utilized as AM, Multicast, Studio Pro or Stereo Generator (see Omnia.ONE SG)
ANALOG I/O	XLR in and out	XLR in and out	XLR in and out	XLR	XLR
AES I/O	XLR in and out	XLR in and out	1 x XLR in and out	Breakout cable	Breakout cable
LIVEWIRE I/O	yes	future	future	yes	yes
SCA IN	yes	yes (RDS only)	yes (RDS only)	not applicable	yes
MPX IN (MONITORING)	no	yes	no	no	no
INTERNAL RDS	no	yes, optional	yes, optional	no	no
MPX OUT	2 x BNC	2 x BNC	2 x BNC	yes	yes
DIGITAL MPX OUT	yes	yes	yes, if HD not in use	no	no
DIVERSITY DELAY	yes	yes	yes	Yes	Yes
FRONT PANEL HEADPHONE OUT	yes	yes	yes	Yes	Yes
FRONT PANEL DISPLAY	10" color touch screen	7" color touch screen	4" color screen	Led Metering and 2.5 x 1 inch monochrome LCD	Led Metering and 2.5 x 1 inch monochrome LCD

OMNIA PROCESSOR COMPARISON

FEATURES	Omnia.11	Omnia.9	Omnia.7	Omnia ONE.SG	Omnia ONE FM
FRONT PANEL CONTROL	touch screen and rotary encoder and HP level	touch screen	Rotary Encoder	Rotary Encoder	Rotary Encoder
ETHERNET	yes	yes	yes	yes	yes
ETHERNET REMOTE	Java browser app	NfRemote windows app	NfRemote windows app	Java browser app	Java browser app
HTTP SERVER-AUTOMATION	no	yes	yes	No	No
PROCESSING ARCHITECTURE	Wideband AGC/parametric EQ/5 band comp/6 band limiter/composite clipper/adjustable crossovers and summing at multiple points.	Undo/6-band Parametric EQ/multi-band noise reduction/input AGC/3 purpose specific wideband AGCs/2-7 band MB AGC + MB Comp + MB Lim	Undo (no adjustments)/4-band Parametric EQ/multi-band noise reduction/input AGC/2 purpose specific wideband AGCs/2-5 band MB AGC + MB Lim	Not applicable	AGC , 4-5 Band AGC, 4-5 band Limiter
CLIPPER	Ultra Low IMD Clipper	Psychoacoustic distortion masking, separate for MPX out and L/R out, Auto Pilot	Final Clipper for FM and Final Limiter for HD	Not applicable	NRSC Compliant Distortion managed Selectable Low Pass
UNDO (DE-CLIPPING AND DE-COMPRESSION)	no	yes, full control	yes, preset selection	no	no
AUTO PILOT (EXTENDS REACH WHEN MONO)	no	yes	no	no	no
STEREO ENHANCER	yes	yes	yes	no	no
SSB	yes	yes	yes	no	no
ITU B.S.412 MPX POWER CONTROL	yes	yes	yes	no	no
PRESET RECALL VIA GPI	yes	yes	yes	no	no
PRESET DAYPARTING	yes	yes	yes	no	no
ANALYSIS TOOLS	no	yes	yes	no	no

THE TELOS ALLIANCE™



For three decades, the companies of The Telos Alliance have revolutionized radio and television audio technology. Our clients range from global networks to local stations, helping them produce better programming to improve audience engagement and ratings.

Our five brands – Telos Systems, Omnia Audio, 25-Seven Systems, Axia Audio and Linear Acoustic – have all developed technologies and products that have raised the bar for quality and innovation in the radio and television industries.

We have reputation for our unique digital audio networking, Audio over IP, telephony, broadcast audio processing, loudness control, audio time management and audio quality monitoring solutions. Our goal is to not only create individual products and technologies that are excellent in their own right but to create systems of products, both inside and across our brands, that lead the industry forward.

Headquartered in Cleveland, Ohio USA, The Telos Alliance has additional US offices, in addition to sales, research and manufacturing offices in Germany, Latvia and China.

Main Office: +1 (216) 241-7225 ▪ **24/7 Support:** +1 (216) 622-0247

Web: telosalliance.com ▪ **Post:** 1241 Superior Avenue, Cleveland OH 44114 USA